


THRASHER A/T IH03



ALL-TERRAIN

The Ironhead Thrasher A/T IH03 is an excellent all-terrain (A/T) tire for light truck, SUV, and crossover drivers. The innovative tread pattern and aggressive sidewall means it can handle your daily commute or weekend off road adventure. The Thrasher A/T IH03 is built to last and designed with comfort in mind so whether you're out for a cruise or an adventure junky heading off-road, these tires provide a smooth and quiet ride. The wide shoulders provide excellent traction in wet conditions and the rim protector adds an extra level of protection for your wheels.



50,000 Mile Limited Treadwear Warranty. See our Warranty for full details.



SEVERE WINTER SERVICE

3PMSF certification denotes a true winter tire, meets severe snow service requirements of RMA/RAC standards.

MULTI- ANGLE LUG DESIGN

Optimizes traction while offering good road manners at the same time.

STAGGERED SCALLOPED SHOULDER LUGS

Provides maximum traction in off road and loose terrain environments

STEPPED LUGS AND STONE EJECTORS

Promotes self-cleaning and extra protection whatever road or path is taken.



THRASHER

A/T IH03



SIZE	PR	LI/SR	T.D.	O.D.	S.W.	R.W.	UTQG	MAX LOAD 1X	MAX LOAD 2X
			32/in.	in.	in.	in.		lbs@psi	lbs@psi
235/75R15		109S	13	28.9	9.3	6.5	600 A B	2271@50	
235/70R16		106S	13	29.0	9.5	7.0	600 A B	2094@44	
245/75R16		111S	13	30.5	9.8	7.0	600 A B	2403@44	
265/70R16	XL	112T	13	30.6	10.7	8.0	600 A B	2469@44	
265/75R16	XL	116S	13	31.7	10.5	7.5	600 A B	2756@44	
235/65R17		104S	13	29.1	9.5	7.0	600 A B	1984@44	
245/65R17		107S	13	29.5	9.8	7.0	600 A B	2149@44	
245/70R17		110T	13	30.6	9.8	7.0	600 A B	2337@44	
265/65R17	XL	112S	13	30.6	10.7	8.0	600 A B	2469@44	
265/70R17	XL	115S	13	31.7	10.7	8.0	600 A B	2679@44	
265/65R18	XL	114T	13	31.5	10.7	8.0	600 A B	2601@44	
275/65R18		116T	13	32.1	11.0	8.0	600 A B	2756@44	
265/50R20	XL	111T	13	30.5	10.9	8.5	600 A B	2403@50	
275/55R20	XL	117T	13	31.9	11.2	8.5	600 A B	2833@50	
275/60R20		115T	13	33.0	11.0	8.0	600 A B	2679@44	
31X10.50R15LT	6PR	109S	16	30.5	10.6	8.5		2270@50	-
LT235/75R15	10PR	104/101R	16	28.9	9.3	6.5		1985@50	1820@50
LT225/75R16	10PR	115/112S	16	29.3	8.8	6.0		2680@80	2470@80
LT235/85R16	10PR	120/116S	16	31.7	9.3	6.5		3042@80	2778@80
LT245/75R16	10PR	120/116S	16	30.5	9.8	7.0		3042@80	2778@80
LT265/75R16	10PR	123/120S	16	31.7	10.5	7.5		3415@80	3085@80
LT285/75R16	10PR	126/123S	16	33.1	11.3	8.0		3750@80	3415@80
LT235/80R17	10PR	120/117R	16	31.8	9.3	6.5		3085@80	2835@80
LT245/70R17	10PR	119/116S	16	30.6	9.8	7.0		3000@80	2755@80
LT245/75R17	10PR	121/118S	16	31.5	9.8	7.0		3195@80	2910@80
LT265/70R17	10PR	121/118S	16	31.7	10.7	8.0		3195@80	2910@80
LT285/70R17	10PR	121/118S	16	32.8	11.5	8.5		3195@80	2910@80
LT265/70R18	10PR	124/121R	16	32.6	10.7	8.0		3525@80	3195@80
LT275/65R18	10PR	123/120S	16	32.1	11.0	8.0		3415@80	3085@80
LT275/70R18	10PR	125/122SR	16	33.2	11.0	8.0		3640@80	3305@80
LT265/60R20	10PR	121/118R	16	32.5	10.7	8.0		3195@80	2910@80
LT275/55R20	8PR	115/112S	16	31.9	11.2	8.5		2680@65	2470@65
LT275/60R20	10PR	123/120R	16	33.0	11.0	8.0		3415@80	3085@80
LT275/65R20	10PR	126/123S	16	34.1	11.0	8.0		3750@80	3415@80
LT305/55R20	10PR	121/118R	16	33.2	12.4	9.5		3195@65	2910@65