

THRASHER MTD01

RUGGED TERRAIN

The Ironhead Thrasher M/T is built to conquer challenging terrain, delivering aggressive off-road performance without sacrificing on-road confidence. Its rugged tread pattern and wide void spacing provide exceptional traction while efficiently clearing mud, dirt, and debris to maintain grip in unpredictable conditions. A reinforced, heavy-duty casing adds durability and stability when the terrain gets tough. From deep mud and rocky trails to everyday city streets, the Thrasher M/T is engineered to deliver strength, control, and dependable performance wherever the road—or trail—takes you.



50,000 Mile Limited
Treadwear Warranty:
LT-metric sizes



60,000 Mile Limited
Treadwear Warranty:
P-metric sizes



TERRAIN DOMINANCE

An ultra-deep, high-void tread pattern featuring an asymmetric staggered lug arrangement maximizes trail bite, while specialized claw-edge blocks dig deep for relentless traction on raw rock and loose shale.

GROUND COMMAND

An engineered wide-contact patch optimizes your vehicle's footprint to deliver unflinching stability and precise steering response, reinforced by a wrap-around sidewall pattern that grips vertical ruts.

TRAIL ARMOR

Built with a heavy-duty, multi-ply reinforced carcass that acts like iron armor against sharp rocks and debris, deflecting impacts to stop flats, sidewall cuts, and tears.



**WET
PERFORMANCE**



**DRY
PERFORMANCE**



**RIDE
COMFORT**



QUIETNESS



**TREAD
LIFE**



THRASHER

MTD01



SIZE	PR	LI/SR	T.D.	O.D.	S.W.	R.W.	MAX LOAD 1X	MAX LOAD 2X
			32/in.	in.	in.	in.	lbs@psi	lbs@psi
LT235/75R15	6PR	104/101Q	19	28.9	9.3	6.5	1985@50	1820@50
LT265/75R16	10PR	123/120Q	20	31.7	10.5	7.5	3415@80	3085@80
LT285/75R16	10PR	126/123Q	20	32.8	11.3	8.0	3750@80	3415@80
LT245/75R16	10PR	120/116Q	19	30.5	9.8	7.0	3042@80	2778@80
LT285/70R17	10PR	126/123Q	21	32.8	11.5	8.5	3750@80	3415@80
LT255/80R17	10PR	123/120Q	20	33.1	10.0	7.0	3415@80	3085@80
LT265/70R17	10PR	123/120Q	20	31.7	10.7	8.0	3415@80	3085@80
LT275/65R18	10PR	123/120Q	21	32.1	11.0	8.0	3415@80	3085@80
LT275/70R18	10PR	125/122Q	21	33.2	11.0	8.0	3640@80	3305@80
LT295/60R20	10PR	126/123Q	21	33.9	11.8	8.5	3750@80	3415@80
LT275/65R20	10PR	126/123Q	20	34.1	11.0	8.0	3750@80	3415@80
LT295/65R20	10PR	129/126Q	20	35.1	11.8	8.5	4080@80	3750@80
31X10.50R15LT	6PR	109Q	20	30.5	10.6	8.5	2270@50	
33X12.50R17LT	10PR	120Q	21	32.5	12.5	10.0	3085@65	
35X12.50R17LT	10PR	125Q	21	34.5	12.5	10.0	3640@65	
33X12.50R18LT	10PR	118Q	21	32.5	12.5	10.0	2910@65	
35X12.50R18LT	10PR	123Q	21	34.5	12.5	10.0	3415@65	
33X12.50R20LT	12PR	119Q	21	32.5	12.5	10.0	3000@80	
35X12.50R20LT	12PR	125Q	21	34.5	12.5	10.0	3640@80	
37X12.50R20LT	10PR	126Q	21	36.5	12.5	10.0	3750@65	
37X13.50R20LT	12PR	128Q	21	36.5	13.6	11.0	3970@80	
35X12.50R22LT	12PR	121Q	21	34.5	12.5	10.0	3195@80	
37X13.50R22LT	12PR	128Q	21	36.5	13.6	11.0	3970@80	
33X12.50R22LT	10PR	109Q	21	32.5	12.4	10.5	2270@65	
37X13.50R24LT	12PR	124Q	21	36.5	13.6	11.0	3525@80	
33X12.50R24LT	10PR	101Q	21	32.5	12.6	11.5	1820@65	
35X12.50R24LT	10PR	111Q	21	34.5	12.4	10.5	2405@65	
35X13.50R26LT	12PR	122Q	21	34.5	13.4	12.0	3305@80	
37X13.50R26LT	12PR	117Q	21	36.5	13.4	12.0	2835@80	